


CVL20i

FACE ATTENDANCE & ACCESS CONTROL TERMINAL







Features

- * Plug and Play Mode, Android OS Based
- * Recognition Distance 0.5m-3m Adjustable by Software
- * Temperature Measurement Optional, Accuracy ±0.3°C
- * Self-Developed Deep Learning Recognition Algorithm With Binocular Camera, 1:1/1:N Multi-Pattern Recognition, Higher Accuracy and Faster Speed
- * Ethernet, Wiegand, Relay, USB Ports Available
- * Multi-Language Software Available, Voice Alarm, Easy for Deployment
- * SDK/API Available for Further Developing

CVL20i


is Suitable for More

Environments

With Built-in IR LEDs

Why CVL20i

Ci-V20 serial face recognition devices are widely used for access control & time attendance system, meanwhile devices can be integrated with temperature detection module. It adopts fast and accurate algorithm and dynamic face recognizable with mask detection, temperature measurement and abnormal alarm functions, can be in standalone mode or online centre management mode. It's important part of security system of buildings, public places, community etc under the global pandemic.



Attendance

of Multiple Branches from

Multiple Locations

any time from any device

Specifications

GENERAL PARAMETER Operation System Android 5.0 Recognition Speed <1s Accuracy 99.90% Working Mode Standalone/ Oline mode switchable HARDWARE PARAMETER Cpu Contex A17 Flash 8-16GB Memory 2-4GB DDR3 Camera Dedicated dual 200MP camera Screen 8 inch HD IPS Sd Card Mircro SD **Expansive Storage 8-128G RECOGNITION PARAMETER** Recognition Mode Face, RFID (optional) **Recording Capacity Face 10000** Recognition Distance 0.5-3m **COMMUNICATION PARAMETER** Communication Ports Ethernet, Wiegand, Relay, USB, Alarm Wireless Communication WIFI (2.4/5G 802.11a/b/g/n/ac), 4G (optional)

APPLICATION SOFTWARE

Apk Free

Desktop Application Yes (Clotix Desktop Attendance-Optional Payroll)

Cloud Base Application Yes (Clotix Cloud Base Attendance App-Optional Payroll, Location Tracking, Café Management,)

Administrator Build-in function

Voice Alarm Yes

Software Language English, Chinese

MECHANIC PARAMETER

Reset 1 reset button

Working Voltage DC12V/3A, 15W

Dimensions (mm)



V20 Turnstile Gate Mode 230 *150 *320mm

V21 Wall-Mounted Mode 230 *150 *320mm

V22 Pole Mounted Mode 230 *150 *1259mm

V23 Desktop Mode 230 *150 *380mm

V24 Cylindrical Gate Mode 128 *48 *495mm





V23 Desktop Mode





V22 Pole Mounted

V24 Cylindrical Gate


Application



Enterprise Buildings Access Control System Self-Service Ticket Management Turnstile Gate System Customs Self-Service Turnstile System

Can be install at Pedestrian Passages in Residential Quarters, Office Buildings, Schools, Government Agencies, Tourist Attractions, Factory Sites, etc

Flow & Configuration





Only Local Area Network Require



Support All Devices Even Smart LED Screens

Website: www.clotix.net Email: contact@clotix.net

